



DECLARATION OF PERFORMANCE

DoP: KCH_CDF-D_004

EN

Unique identification code of the product-type:

SWISSCDF DECOR 6,4mm - 20,2mm; Compact Density Fibreboard

Intended Use/s:

Melamine faced (EN 14322) MDF.H (EN 622-5) for internal use as non-structural components in humid conditions

Manufacturer:

Kronospan Schweiz AG | Willisauerstrasse 37 | CH-6122 Menznau | www.kronospan.com | info@kronospan.com

Authorised representative:

System/s of AVCP:

System 1

Harmonised technical specification

EN 13986: 2004

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of notified certification body that performed the initial inspection of the manufacturing plant and of factory production control, continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance.

Fraunhofer-Institut für Holzforschung WKI
NB 0765

0765-CPR-0884

Notified Body/ies:

certificate of constancy of performance

Declared performance

Essential characteristics	Performance				Test standard
	6-8	10-12	16-19	mm	
Thickness	6-8	10-12	16-19	mm	
Bending strength	60	60	55	N/mm ²	EN 310
Internal Bond	2.0	2.0	2.0	N/mm ²	EN 319
Modulus of elasticity	6000	6000	5500	N/mm ²	EN 310
Swelling in thickness	7	5	5	%	EN 317
Moisture resistance	0.2	0.2	0.2	N/mm ²	EN 1087-1
Formaldehyd Emissions	E1				EN 717-1
Reaction to fire	C-s2, d0				EN 13501-1
Water vapour permeability	NPD				EN 13986
Airborne sound insulation	NPD				EN 13986
Sound absorption	NPD				EN 13986
Thermal conductivity	0.18			W/mK	EN 13986
Biological durability	1+2				EN 13986
Content of Pentachlorophenol	<5			ppm	CEN/TR 14823

NPD: No performance determined

This declaration of performance is issued under the sole responsibility of the manufacturer.
Signed for and on behalf of the manufacturer by:

Roger Braun, COO

(name and function)

Menznau, 27.03.2015

(place and date of issue)

(signature)