



DECLARATION OF PERFORMANCE

DoP: KCH_PB-P3-D_002

EN

Unique identification code of the product-type:

SWISSSPAN P3 Decor 16mm - 40mm

Intended Use/s:

Melamine faced (EN14322) particleboard P3 (EN 312) for internal use as non-structural components in humid conditions

Manufacturer:

Kronospan Schweiz AG | Willisauerstrasse 37 | CH-6122 Menznau | www.kronospan.com | info@kronospan.com

Authorised representative:

System/s of AVCP:

System 4

Harmonised technical specification

EN 13986: 2004

Notified Body/ies:

certificate of constancy of performance

Declared performance

Essential characteristics	Performance					Test standard
	>13-20	>20-25	>25-32	>32-40	mm	
Thickness					mm	
Bending strength	14	12	11	9	N/mm ²	EN 310
Internal Bond	0.45	0.40	0.35	0.30	N/mm ²	EN 319
Modulus of elasticity	1950	1850	1700	1550	N/mm ²	EN 310
Swelling in thickness	14	13	13	12	%	EN 317
Moisture resistance	0.08	0.07	0.07	0.06	N/mm ²	EN 1087-1
Formaldehyd Emissions	E1					EN 717-1
Reaction to fire	D-s2, d0					EN 13501-1
Water vapour permeability	NPD					EN 13986
Airborne sound insulation	NPD					EN 13986
Sound absorption	NPD					EN 13986
Thermal conductivity	NPD					W/mK EN 13986
Biological durability	1+2					EN 13986
Content of Pentachlorophenol	<5					ppm CEN/TR 14823

NPD: No performance determined

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Roger Braun, COO

(name and function)

Menznau, 27.03.2015

(place and date of issue)

(signature)